




匯統國際股份有限公司

Huey Tung International Co.,

# 產品規格書

# Specification

[ Model : HT-01181 / 2012.12.18 version ]



**Cara Audio Corporation**

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: [carawang@hueytung.com.tw](mailto:carawang@hueytung.com.tw) / <http://www.hueytung.com.tw>


# 揚聲器製品規格書 SPEAKER SPECIFICATION

**型號 Model Number:HT-01181**

項目 Items		規格 Specification		
1	公称阻抗 Nominal Impedance	4Ω±15%		
2	最低共振周波数 Lowest Resonance Frequency	950 Hz±20%Hz Without a baffle		
3	实效周波数带域 Effective Frequency Range	F1.2~20KHz -10dB		
4	出力音压 Output Sound Pressure Level	86dB±3dB 1W/1M at (12K,14K,16K,18K)Hz AVE.		
5	入力 Input	定格入力 Rated input 20 W	最大入力 Maximum input 40 W	
6	磁束密度 Flux Density	-----±10% GAUSS		
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 6.32 V		
8	动作试验电压 Operation Test	Must be normal at program source		
9	极性 Polarity	/		
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet:26*6 N35 Sub Magnet:	/G	
11	连续负荷试验 Life Test	Din45573 noise 20 W 96 hours	After the Test, Speaker should be meet the Outside and item 7,8	
12	耐热试验 Heat Resistance	70°C±2°C 20%-25%RH 8Hours and then room temperature 1 hours		
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 8Hours and then room temperature 1 hours		
14	耐寒试验 Cold Resistance			
15	落下试验 Drop Test	1M 75°±2°		
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上		
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing		
18	失真率 Distortion	/		
19	各部 材质	Cone Paper	black silk	
		Voice Coil	/	
		Cap	/	
20	总重量 Total Weight	/		
	Size: 1.1” 試作發行: 2012.9.18	Approve: Arthur	Check: Chen	Design: LIU



成品圖及照片 Mechanical Dimensions :HT-01181



Tolerance:±0.5

Unit: mm

