



匯統國際股份有限公司

Huey Tung International Co., Ltd.

產品規格書

Specification

[Model : HT-6276 / 2013.1.16 version]



Cara Audio Corporation


No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.


Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: carawang@hueytung.com.tw / <http://www.hueytung.com.tw>


揚聲器製品規格書 SPEAKER SPECIFICATION

型號 Model Number: HT-6276

項目 Items		規格 Specification		
1	公称阻抗 Nominal Impedance	4±15% Ω at 200 Hz		
2	最低共振周波数 Lowest Resonance Frequency	55 Hz±20%Hz Without a baffle		
3	实效周波数带域 Effective Frequency Range	F0~9KHz -10dB		
4	出力音压 Output Sound Pressure Level	88dB±2dB 1W/1M at (200,300,400,500)Hz AVE.		
5	入力 Input	定格入力 Rated input 70 W	最大入力 Maximum input 140 W	
6	磁束密度 Flux Density	-----±10% GAUSS		
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 11.8 V		
8	动作试验电压 Operation Test	Must be normal at program source 11.8 V		
9	极性 Polarity	/		
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet: 14+6.7 OZ Sub Magnet:	/G	
11	连续负荷试验 Life Test	PINK noise 70 W 8 hours		
12	耐热试验 Heat Resistance	70°C±2°C 20%-25%RH 8Hours and then room temperature 1 hours		
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 8Hours and then room temperature 1 hours		
14	耐寒试验 Cold Resistance	-25°C±2°C 8Hours and then room temperature 1 hours		
15	落下试验 Drop Test	1M 75°±2°		
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上		
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing		
18	失真率 Distortion	/		
19	各部 材质	Cone Paper	Paper Edge + Paper Body	
		Voice Coil	/	
		Cap	/	
20	总重量 Total Weight	1450 GR		
	Size: 61/2"	Approve:	Check:	Design:
	試作發行: 2009.08.28	Arthur	John	LIU



成品圖及照片 Mechanical Dimensions : HT-6276



Scale:1:1
Toerance:±0.5
Unit:mm