



匯統國際股份有限公司

Huey Tung International Co., Ltd.

# 產品規格書

# Specification

[ Model : HTB-3219 / 2012.11.7 version ]



**Cara Audio Corporation**

No.69, Lane 762, Dingzhong Road, Sanmin District, Kaohsiung City, Taiwan, ROC.

Tel: 886-7-310 5786 / Fax: 886-7-310 0783

E-mail: [carawang@hueytung.com.tw](mailto:carawang@hueytung.com.tw) / <http://www.hueytung.com.tw>

# 揚聲器製品規格書 SPEAKER SPECIFICATION

**型號 Model Number: HTB-3219 (7230)**

項目 Items		規格 Specification			
1	公称阻抗 Nominal Impedance	8Ω±15% at 1000 Hz 1.0v			
2	最低共振周波数 Lowest Resonance Frequency	80 Hz±20%Hz Without a baffle			
3	实效周波数带域 Effective Frequency Range	F0~20KHz -10dB			
4	出力音压 Output Sound Pressure Level	85dB±3dB 1W/1M at (400,600,800,1000)Hz AVE.			
5	入力 Input	定格入力 Rated input 10 W	最大入力 Maximum input 15 W		
6	磁束密度 Flux Density	-----±10% GAUSS			
7	异常音试验电压 Buzz & Rattle Test	Must be normal at sine wave 6.32 V (8Ω 10W)			
8	动作试验电压 Operation Test	Must be normal at program source 8.94 V (8Ω 10W)			
9	极性 Polarity	左正極			
10	磁石尺寸/重量 Magnet Dimension/Weigh	Magnet: Ø60*24*15 Y30 Sub Magnet:	/G		
11	连续负荷试验 Life Test	8.94V (8Ω 10W) PINK NOISE Hours			
12	耐热试验 Heat Resistance	70°C±2°C 20%-25%RH 8Hours and then room temperature 1 hours			
13	耐湿试验 Humidity Resistance	40°C±2°C 90%-95%RH 8Hours and then room temperature 1 hours			
14	耐寒试验 Cold Resistance	-25°C±2°C 24Hours and then room temperature 1 hours			
15	落下试验 Drop Test	1M 75°±2°			
16	绝缘耐压试验 Insulation Resistance	Or more 1MΩ 以上			
17	周波数特性 Frequency Response Curve	参照附图 On Other Drawing			
18	失真率 Distortion	Less than at			
19	各部 材质	Cone Paper	紙盆海棉邊		
		Voice Coil	20.4Ø ASV		
		Cap	/		
20	总重量 Total Weight	/			
		Size: 試作發行: 2007.09.19	Approve: Arthur	Check: Chen	Design: LIU



